

ATLANTICBELT/EUROSLING/EUROBELT

Fasce di sollevamento doppio strato EN 1492-1





DOUBLE PLY POLYESTER WEBBING SLING



Eurosling



Atlanticbelt/Eurobelt

Tipo	Colore	WLL						Peso 1° metro	Peso metro succ.	
		Largh. nastro	Lung. asole							
							0°- 45°			45°- 60°
mm	mm	Kg	Kg	Kg	Kg	Kg	Kg			
ES-01/EB-01	Viola	280	250	1.000	800	2.000	1.400	1.000	0,40	0,25
ES-02/EB-02	Verde	350	250	2.000	1.600	4.000	2.800	2.000	0,44	0,30
ES-03/EB-03	Giallo	350	300	3.000	2.400	6.000	4.200	3.000	0,71	0,50
ES-04/EB-04	Grigio	400	400	4.000	3.200	8.000	5.600	4.000	0,95	0,70
ES-05/EB-05	Rosso	460	400	5.000	4.000	10.000	7.000	5.000	1,20	0,90
ES-06/EB-06	Marrone	600	500	6.000	4.800	12.000	8.400	6.000	1,80	1,20
ES-08/EB-08	Blu	650	500	8.000	6.400	16.000	11.200	8.000	2,30	1,50
ES-10/EB-10	Arancio	700	600	10.000	8.000	20.000	14.000	10.000	2,90	2,00
ES-12/EB-12	Arancio	700	600	12.000	9.600	24.000	16.800	12.000	3,10	2,20
ES-15/EB-15	Arancio	700	600	15.000	12.000	30.000	21.000	15.000	3,10	2,20

ROUND SLING RS-RSR

Anelli tubolari di sollevamento con guaina rinforzata antiusura EN 1492-2

POLYESTER ROUND SLING RS-RSR WITH EXTRA STRONG PU-IMPREGANTED WEBBING OF THE SLEEVE



Tipo	Colore	WLL						Peso x ogni metro lungh.	
		Ø	Largh. guaina						
							0°- 45°		45°- 60°
mm	mm	Kg	Kg	Kg	Kg	Kg	Kg		
RS-01	Viola	15	± 41	1.000	800	2.000	1.400	1.000	0,27
RS-02	Verde	20	± 51	2.000	1.600	4.000	2.800	2.000	0,445
RS-03	Giallo	25	± 53	3.000	2.400	6.000	4.200	3.000	0,56
RS-04	Grigio	30	± 69	4.000	3.200	8.000	5.600	4.000	0,76
RS-05	Rosso	35	± 76	5.000	4.000	10.000	7.000	5.000	0,94
RS-06	Marrone	40	± 80	6.000	4.800	12.000	8.400	6.000	1,12
RS-08	Blu	45	± 90	8.000	6.400	16.000	11.200	8.000	1,54
RSR-10	Arancio	55	± 96	10.000	8.000	20.000	14.000	10.000	2,3
RSR-12	Arancio	55	± 96	12.000	9.600	24.000	16.800	12.000	3,0
RSR-15	Arancio	60	± 110	15.000	12.000	30.000	21.000	15.000	3,4
RSR-20	Arancio	70	± 132	20.000	16.000	40.000	28.000	20.000	4,3
RSR-25	Arancio	80	± 132	25.000	20.000	50.000	35.000	25.000	5
RSR-30	Arancio	90	± 160	30.000	24.000	60.000	42.000	30.000	5,7
RSR-40	Arancio	115	± 160	40.000	32.000	80.000	56.000	40.000	7,2
RSR-50	Arancio	135	± 180	50.000	40.000	100.000	70.000	50.000	9
RSR-60	Arancio	145	± 220	60.000	48.000	120.000	84.000	60.000	10,5
RSR-70	Arancio	150	± 220	70.000	56.000	140.000	98.000	70.000	12
RSR-80	Arancio	160	± 320	80.000	64.000	160.000	112.000	80.000	14
RSR-90	Arancio	165	± 320	90.000	72.000	180.000	126.000	90.000	16
RSR-100	Arancio	170	± 320	100.000	80.000	200.000	140.000	100.000	18