

SCHEDA TECNICA



SERRATURA APPLICARE BLINDATI SERIE 2501 SECUREMME
CON CUORE SECURMAP TRIPLICE CHIUSURA

FISSAGGIO PLANARE/LATERALE | PLANAR/LATERAL FIXING

Mano destra (D) o spingere (R) Right hand (D) or push (R) *	Mano sinistra (S) o tirare (L) * Left hand (S) or pull (L) *	Sporgenza pistoni (S) Projection bolts (S)	Interasse Interspace		N. chiavi N. keys		
250 1 D CR0328S46	250 1 S CR0328S46	3 mm	28 mm	40 mm	3+1T	5	2507
250 1 D CR0328S47	250 1 S CR0328S47	3 mm	28 mm	40 mm	5+1T	5	2508
250 1 D CR0328S56	250 1 S CR0328S56	3 mm	28 mm	50 mm	3+1T	5	2509
250 1 D CR0328S57	250 1 S CR0328S57	3 mm	28 mm	50 mm	5+1T	5	2510
250 1 D CR0328S66	250 1 S CR0328S66	3 mm	28 mm	60 mm	3+1T	5	2513
250 1 D CR0328S67	250 1 S CR0328S67	3 mm	28 mm	60 mm	5+1T	5	2519
250 1 D CR0628S46	250 1 S CR0628S46	6 mm	28 mm	40 mm	3+1T	5	2530
250 1 D CR0628S47	250 1 S CR0628S47	6 mm	28 mm	40 mm	5+1T	5	2582
250 1 D CR0628S56	250 1 S CR0628S56	6 mm	28 mm	50 mm	3+1T	5	2532
250 1 D CR0628S57	250 1 S CR0628S57	6 mm	28 mm	50 mm	5+1T	5	2586
250 1 D CR0628S66	250 1 S CR0628S66	6 mm	28 mm	60 mm	3+1T	5	2536
250 1 D CR0628S67	250 1 S CR0628S67	6 mm	28 mm	60 mm	5+1T	5	2594

* Per ordinare l'articolo con mano R/L
To order the R/L lock

2501 R CR0328S46

* Per ordinare l'articolo in confezione industriale (- 1 €)
To order the lock in industrial packaging (- 1 €)

250 0 DCR0328S46 = 68 €



SECURMAP 24

