

SCHEDA TECNICA

PARIDE

SECUREMME®

SERRATURA APPLICARE BLINDATI SERIE 2451 SECUREMME A DOPPIO CILINDRO TRIPLICE CHIUSURA

FISSAGGIO PLANARE/LATERALE | PLANAR/LATERAL FIXING

Mano destra (D) o spingere (R) * Right hand (D) or push (R)	Mano sinistra (S) o tirare (L) * Left hand (S) or pull (L)	Sporgenza pistoni (S) Projection bolts (S)	Interasse Interspace	 *	 g
254 1 D CR0328CXX	254 1 S CR0328CXX	3 mm	28 mm	5	2743
254 1 D CR0628CXX	254 1 S CR0628CXX	6 mm	28 mm	5	2793
254 1 D CR1328CXX	254 1 S CR1328CXX	13 mm	28 mm	5	2891
254 1 D CR4328CXX	254 1 S CR4328CXX	43 mm	28 mm	5	3261
254 1 D CR0337CXX	254 1 S CR0337CXX	3 mm	37 mm	5	2643
254 1 D CR0637CXX	254 1 S CR0637CXX	6 mm	37 mm	5	2693
254 1 D CR1337CXX	254 1 S CR1337CXX	13 mm	37 mm	5	2791
254 1 D CR4337CXX	254 1 S CR4337CXX	43 mm	37 mm	5	3161

* Per ordinare l'articolo con mano R/L


To order the R/L lock

2541 R CR0328CXX

* Per ordinare l'articolo in confezione industriale (-1 €)

To order the lock in industrial packaging (-1 €)

254 0 DCR0328CXX = 85 €



A richiesta versione con blocco aste (+1 €)
On request block rods model (+1 €)

254 6 DCR0328CXX = 87 €

254 5 DCR0328CXX = 86 €

